ROOFSTONE PAVER LiveRoof LiveRoof Integrated Paver System (Standard) Module Recommended for LiveRoof Standard (4.25") System 1' x 2' x 4" STANDARD **Application COLORS** SIZE ■ BEACH SAND **4**" CHARCOAL **4**" □ LIGHT REFLECTIVE **4**" ■ MOCHA **4**" ■ NATURAL RoofStone Paver (includes concrete Top SIDE VIEWS and black polypropelene Black Polypropylene 4.00 2.00 Use Shim as needed to prevent rocking LiveRoof Standard Module interface with RoofStone Paver with base RoofStone Paver with base RoofEdge at Perimeter if exposed Fasten Edging at Perimeter with Self-**Tapping Screws** TOP/BOTTOM VIEW 12 NOT TO SCALE Paver Weight = 50 lbs (4") or 53 lbs (6") PAVER STD ILLUSTRATIONS ARE TO CONCEPTUALLY ASSIST PROFESSIONALS IN DESIGN OF LIVEROOF APPLICATIONS. LIVEROOF DOES NOT ACCEPT RESPONSIBILITY FOR ENGINEERING BASED ON ILLUSTRATIONS. A QUALIFIED STRUCTURAL ENGINEER SHOULD BE CONSULTED TO DETERMINE APPROPRIATE AND SUITABLE DESIGN. v2024-23-1 PAVER WALKWAYS NEAR PARAPETS SHOULD BE DESIGNED FOR SAFE USE, TAKING INTO ACCOUNT WIND FACTORS.

LiveRoof, LLC P.O. Box 533 Spring Lake, MI 49456

(800) 875-1392 www.liveroof.com LiveRoof